




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61B 5/00	A1	(11) International Publication Number: WO 92/19151 (43) International Publication Date: 12 November 1992 (12.11.92)
<p>(21) International Application Number: PCT/US92/03896</p> <p>(22) International Filing Date: 6 May 1992 (06.05.92)</p> <p>(30) Priority data: 696,585 7 May 1991 (07.05.91) US</p> <p>(71) Applicant: TARGET THERAPEUTICS, INC. [US/US]; 47201 Lakeview Boulevard, Fremont, CA 94537-5120 (US).</p> <p>(72) Inventor: SEPETKA, Ivan ; 1148 Seventeenth Avenue, Redwood City, CA 94063 (US).</p> <p>(74) Agents: CIOTTI, Thomas, E. et al.; Morrison & Foerster, 545 Middlefield Road, Suite 200, Menlo Park, CA 94025 (US).</p>		<p>(81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FI, FR (European patent), GB (European patent), GR (European patent), HU, IT (European patent), JP, KR, LU (European patent), MC (European patent), NL (European patent), NO, SE (European patent).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: CATHETER GUIDE WIRE



(57) Abstract

A catheter guide wire (10) comprising: a flexible, torqueable proximal wire section (13), a more flexible intermediate section (14) with a flexible polymer tube covering (19), and a most flexible distal end section (15). A helical ribbon coil (22) is wrapped about the intermediate core segment between the wire core and the polymer tube covering to increase radiopacity and improve torque transmission while retaining flexibility.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	RU	Russian Federation
CG	Congo	KP	Democratic People's Republic of Korea	SD	Sudan
CH	Switzerland	KR	Republic of Korea	SE	Sweden
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
DE	Germany	MC	Monaco	TC	Togo
DK	Denmark			US	United States of America

-1-

5

CATHETER GUIDE WIREDescriptionTechnical Field

10 This invention is in the general field of surgical instruments and relates specifically to guide wires that are used in cardiovascular and endovascular procedures to facilitate the placement of catheters within the vasculature of patients.

15 Background

The general procedure for placing catheters within vessels is to track a guide wire through the vessel to the desired position and advance the catheter over the guide wire. Guide wires are required because
20 the catheters themselves do not have sufficient column strength or torsional strength to be able to be tracked or steered through the vessel. See, for instance, U.S. Patent No. 4,884,579.

Several types of guide wires for use in
25 catheter placement have been proposed. The simplest type of wire has a preferred diameter of between about 0.20-1.0 mm. The distal end of the wire may be provided with a bent tip which can be oriented, by means of a guide structure at the proximal end, to guide the wire along a
30 selected vascular path. Ideally, torque transmission should be controlled, such that a selected wire rotation at the wire's proximal end produces a corresponding rotation of the distal end. Further, radiopacity is

35

-2-

desired such that a physician may see over the entire vasculature accessed by the guide wire.

The present invention is an improvement on the guide wire assembly described in U.S. Patent No.

5 4,884,579. The prior invention describes a catheter guide wire with three sections with progressively greater flexibility and sliding properties: 1. A semi-rigid, torqueable proximal wire section that is between about 50-250 cm in length, formed of a proximal wire core
10 segment having an outer diameter of between about 0.25-1.0 mm; 2. A more flexible intermediate section that has a length between about 20-60 cm and is formed from an intermediate wire-core segment having a reduced diameter of between about 0.10-0.50 mm, and a low-friction,
15 flexible polymer tube covering which encases the intermediate core segment; and 3. A most distal end section with a length between about 1-10 cm and formed from a distal wire core segment having a reduced diameter of between about 0.05-0.15 mm, and a flexible sleeve
20 covering the distal end segment and providing column strength thereto.

A primary object of the present invention is the improvement of the torque transmission and radiopacity of the above described invention.

25

Disclosure of the Invention

The invention is an improvement to U.S. Patent No. 4,884,579 which describes a catheter guide wire for use within a patient's vasculature comprising in
30 combination:

(a) a flexible, torqueable proximal wire section,

(b) a more flexible intermediate section formed from an intermediate wire-core segment having a
35

-3-

flexible polymer tube covering which encases the intermediate core segment, and

- (c) a most flexible distal end section formed from a distal wire core segment with a helical coil covering the distal end segment and providing column strength thereto.

The improvement comprises a radiopaque helical ribbon coil wrapped about the intermediate core segment between the intermediate wire core and the flexible polymer tube covering. This improvement serves to increase radiopacity and improve torque transmission while retaining flexibility.

Brief Description of the Drawing

In the drawing:

Fig. 1 shows fragmentary portions of a guide wire constructed according to one embodiment of the invention.

Fig. 2 shows fragmentary portions of a guide wire constructed according to another embodiment of the invention.

Like parts are referred to by the same reference numerals in the figures.

Modes for Carrying Out the Invention

Fig. 1 shows a guide wire generally designated 10, constructed according to one embodiment of the invention. The wire is a flexible torqueable wire having an overall length of about 70-300 cm between its proximal and distal ends 11 and 12, respectively, and a maximum outer diameter of between about 0.20-1.0 mm. The major portion of the wire is a flexible proximal section 13 whose overall length ranges from about 50-250 cm. This section is followed by a more flexible intermediate

-4-

section 14 having a length between about 20-60 cm and a most flexible distal end section 15 whose length is between about 1-10 cm.

5 A wire core 16 in the guide wire 10 is formed of a flexible, torqueable wire filament material, such as stainless steel. The diameter of the wire core, at its maximum, is between about 0.20-1.0 mm. The segment of the core forming proximal section 13 of guide wire 10 has a substantially uniform diameter along its length, and corresponds to the maximum diameter of the core, i.e., between 0.20-1.0 mm.

15 Within the intermediate section 14 of the wire, the core is tapered from the proximal-section diameter down to a reduced diameter which is preferably about 0.10-0.50 mm and between about 10%-50% of the diameter of the core's proximal segment 13. Thus, for example, where the proximal section core diameter is 0.46 mm, the core tapers to a minimum of between about 0.05-0.23 mm. The length of tapered segment 17 is typically between about 10%-50% that of reduced-diameter segment 18, and the two segments together make up the length of the intermediate wire section 14, i.e., about 20-60 cm.

25 The wire core 16 of intermediate section 14 is covered along its length by a flexible polymer covering 19. The major function of covering 19 is to provide a low-friction surface along intermediate section 14, and more particularly, a surface which has less friction than the surface of adjacent distal segment 15 and proximal segment 13 (the wire core itself). Covering 19 preferably also functions to provide column support to the reduced-diameter core of the intermediate section, 18, to reduce the tendency of this section to buckle under axial compression.

35

-5-

Covering 19 is preferably formed of a polymer, such as TEFLON™, polyolefin, or polyurethane which can be bonded or otherwise tightly affixed to the core wire, and which itself has a low-friction surface, or can be coated with a low-friction surface. Other suitable coverings include a tube formed from virtually any polymer having exposed hydrogens, such as polyester, polyolefins, polycarbonate, polyvinylchloride, latex or silicon rubber, polystyrene, and polyacrylics, and a surface coating formed of a highly hydrophilic, low-friction polymer, such as polyvinylpyrrolidone (PVP), polyethyleneoxide, or polyhydroxyethylmethacrylate (polyHEMA) or copolymers thereof.

Beneath polymer covering 19, a ribbon of radiopaque metal 22, such as platinum, gold, tungsten, or their alloys is wound around the wire core 16. As shown, the ribbon coil 22 extends from tapered segment 17 of intermediate section 14 at junction 23, to the distal junction 24 of intermediate section 14. The ribbon coil 22 has a thickness of about 0.015 to 0.050 mm, preferably about 0.025 mm and a width of about 0.050 to 0.130 mm, preferably about 0.075 mm. There are approximately 5 to 15 complete turns of ribbon per millimeter of wire core, and preferably about 10 complete turns of ribbon per millimeter of wire core.

The distal section 15 of guide wire 10 is fully or partially encased in flexible sleeve 27. Sleeve 27 shown in Fig. 1 is a soft, flexible helical coil which is formed conventionally, e.g., as a winding of radiopaque wire strand, such as platinum, gold, or tungsten strand. The wire strand has a diameter of about 0.050 to 0.100 mm and preferably about 0.075 mm. As shown, sleeve 27 extends from junction 24 to distal end 12 of guide wire 10. Attachment of the sleeve 27 to wire core 16 is

-6-

preferably by two or three solder or weld joints, one at proximal junction 24 and a second at rounded distal junction 28.

5 In addition to providing a mechanism for wire bending near wire tip 12, sleeve 27 also gives distal section 15 of guide wire 10 increased column strength (in the axial direction), and reduces the chance of buckling in this section with axial compression. At the same time, the combined flexibility of reduced diameter core 10 29 and sleeve 27 are compatible with a series of sharp bends, as the wire is moved through a patient's vasculature. Rounded joint 28 at the end of guide wire 10 acts to shield vessel walls from the sharp end of wire core 16. Further, the distal section of the wire, 15, 15 with the associated sleeve 27, provides the section with a higher frictional coefficient than that of the adjacent intermediate section, 14. The higher-friction surface in this distal section, 15, functions specifically, during a catheter placement operation, to help anchor distal 20 section 15 against a vessel wall at a vessel junction.

Distal wire core 29 has a substantially uniform cross-section. The core may be cylindrical with diameter of between 0.05 and 0.15 mm or flattened with a rectangular cross-section dimensioned 0.025 mm by 0.075 25 mm. The wire core has a tapered section at junction 24 that covers between about 10-50% of the core's distal segment.

Fig. 2 is another embodiment of the invention that is essentially the same as Fig. 1 except for the 30 replacement of a portion of helical ribbon coil 22 with inner wire coil 35. At the distal end of helical ribbon coil 22, there is a soft flexible helical coil 24 which is formed conventionally, e.g., as a winding of radiopaque wire strand, such as platinum, gold or 35

-7-

tungsten. As shown, coil 35 extends from helical ribbon coil 22 at junction 36 to the proximal end of distal segment 15 at junction 24. This inner coil 35 serves as an anchor point for the distal end of flexible helical coil 22 and also as an anchor point for the polymer covering 19 on intermediate core section 14.

10

15

20

25

30

35

-8-

Claims

1. In a catheter guide wire for use within a
5 patient's vasculature comprising in combination:

(a) a semi-rigid, torqueable proximal wire
section,

(b) a more flexible intermediate section
formed from an intermediate wire-core segment having a
10 flexible polymer tube covering which encases the
intermediate core segment, and

(c) a most flexible distal end section formed
from a distal wire core segment with a helical coil
covering the distal end segment and providing column
15 strength thereto,

the improvement comprising a radiopaque helical
ribbon coil wrapped about the intermediate core segment
between the intermediate core segment and the flexible
polymer tube covering.

20

2. The guide wire of claim 1 wherein the
ribbon coil is formed from a radiopaque metal selected
from the group consisting of platinum, gold, tungsten and
their alloys.

25

3. The guide wire of claim 1 wherein the
ribbon coil is a tightly wound coil with a thickness of
about 0.015 to 0.050 mm and a width of about 0.050 to
0.130 mm, which extends from the proximal wire section of
30 the guide wire to the junction of the distal wire core
segment.

35

-9-

4. The guide wire of claim 1 wherein:

(a) the flexible, torqueable proximal wire section has an outer diameter of between about 0.25-0.10 mm, and

5 (b) the intermediate wire core segment has a reduced diameter of between about 0.10-0.50 mm, and

(c) the distal wire core segment has a reduced cross-sectional area.

10 5. The guide wire of claim 4 wherein the distal wire core segment is cylindrical and has a diameter of between about 0.05 and 0.15 mm.

15 6. The guide wire of claim 4 wherein the distal wire core segment is rectangular with cross-sectional dimensions of 0.025 mm by 0.075 mm.

7. The guide wire of claim 1 wherein:

20 (a) the flexible, torqueable proximal wire section has an outer diameter of between about 0.25-0.50 mm, and

(b) the intermediate wire core segment has a reduced diameter of between about 0.10-0.20 mm, and

25 (c) the distal wire core segment has a reduced diameter of between about 0.05-0.13 mm.

8. In a catheter guide wire for use within a patient's vasculature comprising in combination:

30 (a) a flexible, torqueable proximal wire section,

(b) a more flexible intermediate section formed from an intermediate wire-core segment having a flexible polymer tube covering which encases the intermediate core segment, and

35

-10-

(c) a most flexible distal end section formed from a distal wire core segment with a helical coil covering the distal end segment and providing column strength thereto,

5 the improvement comprising a radiopaque helical ribbon coil wrapped about the intermediate core segment between the intermediate core segment and the flexible polymer tube covering wherein a platinum helical coil
10 serves as an anchor point for the proximal end of the distal helical coil and the anchor point for the distal end of the flexible polymer tube covering which encases the intermediate core segment and the helical ribbon
15 coil.

20

25

30

35

FIG. 1





FIG. 2



SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US92/03896

A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) :A61B 5/00

US CL :128/772

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 128/657; 604/95, 164, 283

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

none

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US,A, 4,884,579 (Engelson) 05 December 1989 (See entire reference).	1-5,7,8
Y	US,A, 4,964,409 (Tremulis) 23 October 1990 (See entire reference).	1-5,7,8
Y	US,A, 4,003,369 (Heilman et al.) 18 January 1977 (See figure 2a-2c).	6

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be part of particular relevance	X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	Z* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search 23 JULY 1992	Date of mailing of the international search report 16 OCT 92
Name and mailing address of the ISA/ Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. NOT APPLICABLE	Authorized officer <i>my name</i> MAX HINDENBURG Telephone No. (703) 308-0858


(51) International Patent Classification ⁵ : A61B 5/00	A1	(11) International Publication Number: WO 92/19151
		(43) International Publication Date: 12 November 1992 (12.11.92)

(74) Agents: CIOTTI, Thomas, E. et al.; Morrison & Foerster,
545 Middlefield Road, Suite 200, Menlo Park, CA 94025
(US).

(81) Designated States: AT (European patent), AU, BE (European patent), CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FI, FR (European patent), GB (European patent), GR (European patent), HU, IT (European patent), JP, KR, LU (European patent), MC (European patent), NL (European patent), NO, SE (European patent).

Date of publication of the amended claims and statement:
23 December 1992 (23.12.92)

(54) Title: CATHETER GUIDE WIRE



A catheter guide wire (10) comprising: a flexible, torqueable proximal wire section (13), a more flexible intermediate section (14) with a flexible polymer tube covering (19), and a most flexible distal end section (15). A helical ribbon coil (22) is wrapped about the intermediate core segment between the wire core and the polymer tube covering to increase radiopacity and improve torque transmission while retaining flexibility.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

AMENDED CLAIMS

[received by the International Bureau on 27 November 1992 (27.11.92);
original claims 1 and 8 amended; remaining claims unchanged (3 pages)]

1. In a catheter guide wire for use within a patient's vasculature comprising in combination:
 - (a) a semi-rigid, torqueable proximal wire section,
 - (b) a more flexible intermediate section formed from an intermediate wire-core segment having a flexible polymer tube covering which encases the intermediate core segment, and
 - (c) a most flexible distal end section formed from a distal wire core segment with a helical coil covering the distal end segment and providing column strength thereto, the improvement comprising a radiopaque helical ribbon coil wrapped about the intermediate core segment between the intermediate core segment and the flexible polymer tube covering so to improve torque transmission and increase radiopacity of the intermediate section over that of the bare intermediate core segment without substantially increasing its stiffness.
2. The guide wire of claim 1 wherein the ribbon coil is formed from a radiopaque metal selected from the group consisting of platinum, gold, tungsten and their alloys.
3. The guide wire of claim 1 wherein the ribbon coil is a tightly wound coil with a thickness of about 0.015 to 0.050 mm and a width of about 0.050 to 0.130 mm, which extends from the proximal wire section of the guide wire to the junction of the distal wire core segment.

4. The guide wire of claim 1 wherein:
(a) the flexible, torqueable proximal wire section has an outer diameter of between about 0.25-0.10 mm, and
(b) the intermediate wire core segment has a reduced diameter of between about 0.10-0.50 mm, and
(c) the distal wire core segment has a reduced cross-sectional area.

5. The guide wire of claim 4 wherein the distal wire core segment is cylindrical and has a diameter of between about 0.05 and 0.15 mm.

6. The guide wire of claim 4 wherein the distal wire core segment is rectangular with cross-sectional dimensions of 0.025 mm by 0.075 mm.

7. The guide wire of claim 1 wherein:
(a) the flexible, torqueable proximal wire section has an outer diameter of between about 0.25-0.50 mm, and
(b) the intermediate wire core segment has a reduced diameter of between about 0.10-0.20 mm, and
(c) the distal wire core segment has a reduced diameter of between about 0.05-0.13 mm.

8. In a catheter guide wire for use within a patient's vasculature comprising in combination:
(a) a flexible, torqueable proximal wire section,
(b) a more flexible intermediate section formed from an intermediate wire-core segment having a flexible polymer tube covering which encases the intermediate core segment, and

(c) a most flexible distal end section formed from a distal wire core segment with a helical coil covering the distal end segment and providing column strength thereto,

the improvement comprising a radiopaque helical ribbon coil wrapped about the intermediate core segment between the intermediate core segment and the flexible polymer tube covering so to improve torque transmission and increase radiopacity of the intermediate section over that of the bare intermediate core segment without substantially increasing its stiffness and wherein a platinum helical coil wrapped around the proximal end of the distal section serves as an anchor point for the proximal end of the distal helical coil and the anchor point for the distal end of the flexible polymer tube covering which encases the intermediate core segment and the helical ribbon coil.

STATEMENT UNDER ARTICLE 19

In the International Search Report, the claims are said not to involve an inventive step, in one fashion or another, over two references. The primary references are Engelson (U.S. patent no. 4,884,579) and Tremulis (U.S. patent no. 4,964,409). The propriety of using Engelson is not in

question here. The claims are in an improvement format, the preamble of the claim certainly is thoroughly described in the Engelson patent.

It is with Tremulis that issue is taken, particularly with the claims as now recited. The Tremulis reference describes a hollow "guiding member". Figure 6 is exmpletive of the reference. The guiding portions of the Tremulis device appear to include a main tubular member (10) which is brazed, welded, soldered, or glued via a joint (18) to a core member (14) which eventually passes to the distal end of a balloon (40) and terminates in a "location" (43). A radiopaque coil (45) is placed at the distal end of the tubular extension (12) in its adhesive joint with balloon (40). There is no suggestion anywhere within Tremulis that the balloon is suitable for transmitting any torque. Indeed it appears that the concept of including core member (14) is for the specific purpose of transmitting torque applied at the proximal end of the torque tube (or "tubular member" 10). See, for instance, column 6, lines 46 and following. Marker coil (45) is not in a position to functionally add to the torque carrying capacity of the device disclosed in the Tremulis reference nor specifically, is it able to increase the torque handling capabilities of what might said to be the guide "wire" in Tremulis -- core member (14).

Consequently, the additionally emphasized capability of the ribbon wrapping upon the middle portion of applicant's guide wire -- both enhanced torque transmission and radiopacity -- should provide the information needed to permit removal of the Engelson and Tremulis references as "particularly relevant."

Claim 6 is said not to contain a relevant step over Engelson in view of Tremulis and further in view of Heilman et al. (U.S. Patent 4,003,369). Applicant agrees that

Heilman et al. teaches a guide wire having a rectangular cross-section. However, in view of the deficiency of Tremulis as discussed above, the overall combination of the three references is insufficient to form the basis upon which an appropriate holding of lack of inventive step may be based.

Withdrawal of such a holding is similarly requested.

FIG. 1





FIG. 2



SUBSTITUTE SHEET

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.